



## ▶ VALKYRIE VOX A<sup>II</sup>

### Addressable Voice Sounder

Available in 2 colours

The **VALKYRIE VOX A** is a wall mounted **Addressable Voice Sounder** which is available in either **Red or White** housings. The VALKYRIE VOX voice sounder is based on our successful Horn type sounder and sounder/ beacon. Up to 32 individually addressed sounders can be installed per loop occupying an address in the range 94 to 125, it can be also configured the shadow mode. The address is set using switches 1 to 5 of the 8 way DIL switch.

With message selection directly programmable via the standard sounder programming of the **JUNIOR and JUNO-NET Panels**, the VALKYRIE VOX A, can broadcast up to **5 differentiated pre-loaded messages: Alert, Fire, Evacuation, Test and Silence Message**. The desired messages can be downloaded from our own **proprietary recording PC application**, via a standard **USB interface**. This product is Loop Controlled and Loop Powered.

### Key Features

- ▶ Multi-Message. Follows Panel's Sounder Programming
- ▶ Multi-Language
- ▶ 107 dBA maximum sounder output at 1 m
- ▶ Messages easily programmed via USB interface using dedicated software
- ▶ Synchronization for fast activation

TECHNICAL SPECIFICATIONS	VALKYRIE VOX A
SUPPLY VOLTAGE	Loop: 20 V to 30 V DC
LOOP CURRENT	0.7 mA (Quiescent) - 7.5 mA Max. (sounder active or charging)
LOOP CURRENT - ALARM BEACON	1.4 mA
SOUND OUTPUT @ 1 METER	Tone 104 dBA - Voice Message 107 dBA
MAX. CABLE SIZE	2.5 mm <sup>2</sup>
COLOUR / CASE MATERIAL	Red or White / ABS
OPERATING TEMPERATURE / MAX. HUMIDITY	-10°C to 50°C / 95% RH Non-Condensing
PROTECTION	IP21C - Type A - Indoor use
DIMENSIONS / WEIGHT	109.5 (D) x 83.6 (H) mm / 270 g - 325 g including packaging
ORDER CODE	DESCRIPTION
<b>VALKYRIE VOX A</b>	VALKYRIE VOX - ADDRESSABLE
<b>VALKYRIE VOX AB</b>	VALKYRIE VOX - ADDRESSABLE - WITH BEACON